



Declaration of compliance

Item number: 70075 - Small mixer, 890 mm
Item name: 70095 - Mixer, 1175 mm

Business operator: **Vikan A/S**
Rævevej 1
7800 Skive
Denmark
Tel.: +45 96 14 26 00

Materials: **Polyamid (nylon) 97 % and white masterbatch 3 %**

Polyamid

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011) and 1282/2011 (10. December 2011) are included.

Hexamethylenediamine with specific migration limit (SML) 2.4 mg/kg is used.
We found that the product meets the requirement regarding this SML by product testing.

White masterbatch

Monomers and additives used to manufacture this grade are listed in Commission Regulation (EU) No. 10/2011 of 14. January 2011 on plastic materials and articles intended to come into contact with foodstuffs. Current amendments 321/2011 (1. April 2011), 1282/2011 (10. December 2011) and 1183/2012 (31. November 2012) are included.

White masterbatch contains the following "dual use" additive: TiO2.

Monomers and additives with specific migration limit (SML) are used. It is to be determined at the moment.

FDA: All raw materials in this product are in compliance with FDA (Food and Drug Administration in the USA) CFR 21.

EU commission: In accordance with EU Commission Regulation no. 1935/2004 of October 2004 the product is intended for food contact. The handle can be marked with the "glass & fork" symbol on the packaging or by labeling.

The product is produced according to EU Commission Regulation no. 2023/2006 of 22. December 2006 on good manufacturing practices for materials and articles intended to come into contact with food (GMP).

Overall migration tests is made on this product. The product meets the requirements regarding overall migration to Isooctane (as a substitute to olive oil).

Food contact: The finished article may not be used in contact with alcohol.

Usage temperature: Min. temp.: -20 °C
Max. temp.: 170 °C

General: It is recommended that equipment is cleaned, disinfected and sterilised, as appropriate to it's intended use, before use.
It is also important to clean, disinfect and sterilise equipment after use, using the appropriate decontamination chemicals, concentrations, times and temperatures.
Appropriate equipment decontamination will minimise risk of microbial growth and cross contamination and maximise the efficiency and durability of the equipment.

Wash temp.: 121 °C

Date: 19th March 2014

Made by: Inger Arensbach
Quality- and environmental manager